






-  4.0 Kg/m
-  M
-  ALU/BLACK
-  (RFID)  
READY
-  P.100

## Triangle - M29TX

Code	Length
112001	21 cm
112002	25 cm
112003	29 cm
112004	50 cm
112005	71 cm
112006	100 cm
112007	150 cm
112008	200 cm
112009	250 cm
112010	300 cm
112012	400 cm

## Load table M29TX


Span m	CPL kg	Deflection mm	2 x load kg	Deflection mm	3 x load kg	Deflection mm	4 x load kg	Deflection mm	UDL kg/m	Deflection mm
2.0	813.0	3	557.0	4	449.0	4	349.7	4	847.0	4
4.0	444.8	12	317.5	16	234.6	15	188.6	16	248.1	16
6.0	302.2	28	219.5	36	156.6	33	127.5	36	108.4	35
8.0	225.4	50	165.6	64	115.7	59	94.9	64	59.5	62
10.0	176.6	78	130.9	99	90.1	92	74.3	99	36.8	97
12.0	142.3	112	106.4	143	72.3	133	59.9	143	24.5	140
14.0	116.5	152	87.9	194	59.1	181	49.1	194	17.1	190
16.0	96.2	199	73.3	254	48.6	236	40.6	254	12.3	248
20.0	65.4	311	49.8	397	32.9	369	27.7	397	6.6	388

## Cantilever load

Span m	1 x Load kg	Deflection mm	UDL kg/m	Deflection mm
0.5	708.0	0	1697.3	0
1.0	406.0	1	706.1	2
1.5	287.6	5	338.2	4
2.0	221.8	11	201.0	8
2.5	179.8	22	132.7	12
3.0	150.5	39	93.7	18
3.5	128.8	62	69.4	25
4.0	112.0	92	53.2	34

## Multiple supported span

Span m	CPL kg	Deflection mm	2 x load kg	Deflection mm	UDL kg/m	Deflection mm
2.0	953.3	1	530.5	1	676.9	1
4.0	545.4	6	301.6	5	191.9	5
6.0	379.6	14	210.9	13	90.7	12
8.0	286.5	25	159.6	23	51.9	21
10.0	226.1	39	126.2	36	33.0	33
12.0	183.0	55	102.3	50	22.3	47
14.0	150.3	71	84.1	65	15.8	61
16.0	124.3	88	69.6	80	11.5	75
20.0	84.7	117	47.4	107	6.3	117

 Find complete loading tables on [SIXTY82.nl](http://SIXTY82.nl)

All loading data is based on calculations per EN-1999-1-1 and the following assumptions:

- Static loads only.
- Spans supported or suspended at both ends.
- Triangle trusses solely used apex-up, apex-down.
- 2 chords truss to be placed upright, supported from top chord and loaded from bottom chord.
- Truss spans can be constructed of elements of different length.

- Interaction between bending moment and shear force considered.
- Self-weight of truss is already considered.
- Assembled truss systems need an individual structural calculation. Please contact SIXTY82 or a structural engineer.
- Read the manual before use.
- Higher loading can be allowed depending on the truss configuration.